










UniLift DHM-500 (Chart of dimensions)

Rated Load	Entrances	Door Clearance	CABIN dimensions		Required SHAFT		Lift STRUCTURE	
270 kg	single	700	880	785	1.000	1.000	1.070	1.075
270 kg	single	700	900	900	1.020	1.115	1.090	1.190
270 kg	double 90°	700 / 800	900	900	1.115	1.000	1.185	1.065
270 kg	double 180°	800	900	900	1.140	970	1.210	1.040
315 kg 	single	800	900	1.250	1.020	1.465	1.090	1.540
315 kg 	double 90°	800 / 900	900	1.250	1.115	1.350	1.185	1.415
315 kg 	double 180°	800	900	1.250	1.140	1.320	1.210	1.390
385 kg 	single	900	1.100	1.400	1.220	1.615	1.290	1.690
385 kg 	double 90°	900	1.100	1.400	1.315	1.500	1.385	1.565
385 kg 	double 180°	900	1.100	1.400	1.340	1.470	1.410	1.540
495 kg 	single	900	1.100	1.800	1.220	2.015	1.290	2.190
495 kg 	double 90°	900	1.100	1.800	1.315	1.900	1.315	1.965
495 kg 	double 180°	900	1.100	1.800	1.340	1.870	1.410	1.940

Other dimensions, in accordance with available shaft dimensions.